



One (1)

5 YEAR ALUMINUM BODY WARRANTY

Central States Fire Apparatus LLC (CSFA) warrants to the original purchaser only, that the all aluminum body, fabricated by Central States Fire Apparatus, under normal use and with reasonable maintenance, be structurally sound and will remain free from corrosion perforation for a period of FIVE (5) years.

This warranty does not apply to the following items that are covered by a separate warranty: paint finish, hardware, moldings, and other accessories attached to this body. In addition, this warranty does not apply to any part or accessory manufactured by others and attached to this body.

CENTRAL STATES FIRE APPARATUS MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE ALUMINUM BODY AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND HEREBY DISCLAIMED.

Central States Fire Apparatus will replace without charge, repair or make a fair allowance for any defect in material or workmanship demonstrated to its satisfaction to have existed at the time of delivery or not due to misuse, negligence, or accident. If Central States Fire Apparatus elects to repair this body, the extent of such repair shall be determined solely by Central States Fire Apparatus, and shall be performed solely at the Central States Fire Apparatus factory, or at an approved facility. The expense of any transportation to or from such repair facility shall be borne by the purchaser and is not an item covered under this warranty.

Central States Fire Apparatus will not be liable for damages and under no circumstances will its liability exceed the price for a defective body. The remedies set forth herein are exclusive and in substitution for all other remedies to which the purchaser would otherwise be entitled.

Central States Fire Apparatus will be given a reasonable opportunity to investigate all claims. The purchaser must commence any action arising out of, based upon or relating to agreement or the breach hereof, within twelve months from the date the cause of the action occurred.

One (1)

PAINT WARRANTY

The PPG paint performance guarantee will cover the areas of the vehicle finished with the specified product for a period of FIVE (5) years beginning the day the vehicle is delivered to the purchaser.



The areas as outlined on the Guarantee Certificate, will be covered for the following paint failures:

GUARANTEE INCLUSIONS:

FULL APPARATUS BODY MANUFACTURED AND PAINTED BY CENTRAL STATES FIRE APPARATUS:

- * Peeling or delamination of the topcoat and/or other layers of paint.
- * Cracking or checking.
- * Loss of gloss caused by cracking, checking, or hazing.
- * Any paint failure caused by defective PPG Fleet Finishes which are covered by this guarantee.

All guarantee exclusions, limitations, and methods of claims are covered in the full certificate provided to the original purchaser.

One (1)

STEP SURFACE

The commercial chassis step area on the driver's side shall have slip resistant overlay material installed on each step surface.

One (1)

STEP SURFACE

The commercial chassis step area on the passenger side shall have slip resistant overlay material installed on each step surface.

One (1)

STEP TYPE FUEL TANK

There shall be a step type fuel tank furnished with the chassis.

One (1)

FRONT MUD FLAPS

Heavy-duty, white colored, rubber mud flaps shall be furnished and installed behind the front wheels of the vehicle. Mud flaps shall extend the full width of the front tires and are to be attached with stainless steel fasteners.

One (1)

REAR MUD FLAPS

Heavy-duty, white colored, rubber mud flaps shall be furnished and installed behind the rear wheels of the vehicle. Mud flaps shall extend the full width of the rear duals and are to be attached with stainless steel fasteners.

One (1)



HORIZONTAL CHASSIS EXHAUST

One (1) The chassis exhaust system shall be extended to the front of the right rear wheel.

ALTERNATOR

One (1) The alternator shall be of adequate size to meet the NFPA requirements and to accommodate the specific apparatus electrical load.

WATEROUS CG-500 GPM SINGLE STAGE FIRE PUMP

One (1) The centrifugal type fire pump shall be a Waterous model CG midship mounted with a rated capacity of 500 GPM. The pump shall meet NFPA 1901 requirements. The pump shall have a PTO drive gearbox.

SINGLE STAGE MIDSHIP MOUNTED FIRE PUMP

A Waterous Model CGK fire pump shall be midship mounted, single stage centrifugal type. In addition to meeting NFPA 1901 requirements, it shall be constructed and mounted in accordance with the following specifications.

Fire pump shall incorporate direct mount, high strength, gear drive transmission.

Fire pump shall be driven by a heavy duty 10 bolt PTO capable of enough torque to operate the fire pump at rated capacity for continuous duty. The PTO shall be approved by Allison for this type of service. The PTO shall be of a "Hot Shift" style capable of either full capacity stationary pumping or pump and roll. Stationary pumping shall be done with chassis transmission in neutral.

At time of delivery the pump shall be tested and rated as follows:

- 100% of rated capacity at 150 pounds net pressure
- 70% of rated capacity at 200 pounds net pressure
- 50% of rated capacity at 250 pounds net pressure
- 100% of rated capacity at 165 pounds net pressure

The pump casing shall be a three-piece, vertically split design, high strength gray iron.

The impeller shaft shall be stainless steel, heat treated, and precisely machined and ground to size. All bearings are to be oil or grease lubricated, ball-type, located outside the pump casing in the pump transmission, to accurately align and support the impeller shaft assembly and input shaft. Ball bearings are to be deep groove type, designed to carry both radial and axial loads. A face-type, self-adjusting, corrosion and wear resistant mechanical seal is to be provided.



The pump must be tested by the pump manufacturer for 10 minutes hydrostatically at a pressure of 500 psig. Certification by the pump manufacturer must be provided.

The pump shall be provided with a plate giving the rated flow at "capacity" and "pressure" test pressures, together with the R.P.M. of the engine at those pressures and deliveries and mounted in clear view of the pump operators panel. Data plate shall include model and serial numbers of the pump body and chain transmission, hydro and discharge test pressures, and the date of pump and transmission manufacture.

All pump components including relief valve, pump shift and priming system shall be manufactured by the Waterous Company to insure sole source responsibility and engineered compatibility.

PRIMING SYSTEM:

The pump shall be capable of taking suction and discharging water with a lift of 10 feet in not more than 30 seconds with the pump dry, through 20 feet of suction hose of appropriate size. It shall be capable of developing a vacuum of 22" at an altitude of up to 1000 feet.

A vacuum test with a capped suction of at least 20' long shall develop 22" of vacuum and hold a vacuum with a drop not in excess of 10" in 5 minutes.

One (1)

VPE PRIMING SYSTEM

A high capacity, electrically driven Waterous model VPE rotary vane priming pump shall be provided mounted in the pump compartment.

The priming system shall include a one-gallon oil reservoir tank that is conveniently located behind a hinged access door. Priming tank shall be properly vented so as to provide priming pump lubrication.

One (1)

MANUAL CONTROL PRIMING PUMP

Priming pump shall be activated by a mechanical/electric valve with a single pull control located at the pump operators panel area. Valve actuation may be accomplished while the main pump is operational, if necessary to assure a complete prime.

One (1)

MECHANICAL SHAFT SEAL

The pump shall be equipped with self-adjusting, maintenance free, "Mechanical Shaft Seal" which is designed to be functional in the unlikely event of a seal



failure. Pumps with packing which requires periodic adjustment and/or replacement will not be acceptable.

One (1)

DISCHARGE PRESSURE RELIEF VALVE

Pump pressure shall be controlled by a Waterous Fire Pump Company automatic relief valve that is capable of operation over a range of 75 to 300 psi net pump pressure. The Relief Valve shall be controlled at the pump operator's position. Relief valve shall have two controls, one for pressure adjustment and the other an on/off control. Pilot valve shall maintain set pressure until manually reset by the pump operator. Relief valves requiring pressure reset after each use of the pump are not acceptable.

Relief pilot valve orifice shall be protected from malfunction due to sand or other sediment in the water by a strainer that can be removed, cleaned, and replaced at the operator's panel while the pump is operating. Relief valves which require orifice cleaning within or below the pump enclosure are not acceptable.

Operators panel mounted relief valve indicator lights shall be provided. Lights shall include two color-indicating lights to show position of relief valve. A green light shall indicate a fully closed relief valve and an amber light shall display when the valve begins to open.

Relief valves requiring pressure reset after each use of the pump does not meet the technical fireground operational requirement of these specifications.

One (1)

MANIFOLD DRAIN:

A manifold drain valve shall be furnished with all pump drains connected to it so that the entire pump system may be drained by one control.

Drain valve assembly shall consist of a stainless steel plunger and a bronze body rigidly attached to the fire pump transmission.

A push-pull control with chrome plated "T" handle is to be provided and located at the drivers side of the pump house, properly identified as MASTER DRAIN.

One (1)

FIRE PUMP WARRANTY

The Waterous fire pump shall carry the pump manufacturer's two (2) year warranty covering defective parts and workmanship. A copy of the pump manufacturer's warranty policy shall be provided with the completed apparatus.

One (1)

UL TEST



The pump shall undergo an Underwriters Laboratories Incorporated test per Class A requirements of NFPA #1901 prior to delivery of the completed apparatus. The UL acceptance certificate shall be furnished with the apparatus on delivery.

One (1)

PUMP COOLING LINE

A 3/8" cooling line shall be installed to recirculate water from the pump back to the water tank, to cool the pump during pro-longed pumping operations. The cooling line shall be controlled at the operator's position with a quarter turn valve.

One (1)

HEAT EXCHANGER

A heat exchanger shall be provided on the pump driving engine cooling system. The heat exchanger shall not allow mixing of the pump driving engine coolant and water from the fire pump.

A gated line shall be installed to provide water from the fire pump to the pump driving engine heat exchanger to assist in engine cooling during pumping operations. The heat exchanger line shall be controlled at the pump operator's panel.

One (1)

PUMP SHIFT INDICATOR LIGHTS

Fire pump shall be driven by a heavy duty 10 bolt PTO capable of enough torque to operate the fire pump at rated capacity for continuous duty. The PTO shall be approved by Allison for this type of service. The PTO shall be of a "Hot Shift" style capable of full capacity stationary pumping. Stationary pumping shall be done with chassis transmission in neutral. Pump engagement lights and safety interlock system for PTO driven pumps that are to be used for Stationary Pumping Only with the transmission in neutral shall be as follows:

- A "Pump Engaged" indicator light shall be provided both in the driving compartment and on the pump operator's panel to indicate that the pump shift has been successfully completed.
- An "OK to Pump" indicator light shall be provided in the driving compartment to indicate that the pump is engaged, the chassis transmission is in neutral, and the parking brake is engaged.
- A "Throttle Ready" indicator shall be provided at the pump operator's panel that is energized when the "OK to Pump" indicator is energized or when the chassis transmission is in neutral and the parking brake is engaged.
- An interlock system shall be provided to prevent advancement of the engine speed at the pump operators panel unless the chassis transmission is in neutral and the parking brake is engaged, or the apparatus is in "OK to Pump" mode.



· Controls to engage the PTO are to be in the cab, and easily accessible.

One (1)

WATEROUS PTO PUMP INSTALLATION

The Waterous PTO fire pump shall be installed in conjunction with the body manufacturing process. Fire pump installation shall include installation of the fire pump, modification and/or fabrication of new drivelines and all pump-mounting brackets. PTO drive shaft(s) shall be spin balanced prior to final installation.

One (1)

HOT DIP GALVANIZED INTAKE MANIFOLD

The suction manifold shall be fabricated from heavy-duty tubular steel. The suction manifold shall have radiused sweep elbows to minimize water turbulence into the suction volute. The suction manifold shall be welded and pressure tested prior to the galvanizing process. After testing the entire suction manifold shall be hot dip galvanized to minimize corrosion. The hot dip galvanized suction manifold shall be attached to the pump intake volute with a heavy-duty, flexible victaulic coupling.

The hot dip galvanized manifold assembly shall have a ten (10) year warranty.

One (1)

DRIVERS SIDE STEAMER INLET

There shall be one (1) steamer inlet furnished on the driver's side of pump panel. The suction inlet shall have 4" NST thread. The suction inlet shall have a removable strainer provided inside the external inlet.

Steamer inlet to be as short as possible to allow suction fittings to be attached without extending past the side running boards.

One (1)

PASSENGER SIDE STEAMER INLET

There shall be one (1) steamer inlet furnished on the passenger side of pump panel. The suction inlet shall have 4" NST thread. The suction inlet shall have a removable strainer provided inside the external inlet.

Steamer inlet to be as short as possible to allow suction fittings to be attached without extending past the side running boards.

One (1)

SUCTION CAP DRIVER'S SIDE

The driver's side suction inlet shall be equipped with a chrome-plated, long handled, cap capable of withstanding 500 PSI.

One (1)

SUCTION CAP PASSENGER SIDE



The passenger's side suction inlet shall be equipped with a chrome-plated, long handled, cap capable of withstanding 500 PSI.

One (1)

2-1/2" GATED SUCTION INTAKE DRIVER SIDE

A 2-1/2" independent gated suction intake shall be provided on the driver's side pump panel. Intake shall be provided with a quarter-turn valve and control. The intake shall have a 3/4" drain valve with handle. Each intake shall have chrome-plated female swivel adapter with removable internal screen and a chrome-plated plug type cap with end chain.

One (1)

SUCTION VALVE CONTROL

Suction valve shall have swing type control handle located adjacent to valve.

One (1)

2-1/2" GATED SUCTION INTAKE PASSENGER SIDE

A 2-1/2" independent gated suction intake shall be provided on the passenger's side pump panel. Intake shall be provided with a quarter turn-valve and control. The intake shall have a 3/4" drain valve with handle. Each intake shall have chrome-plated female swivel adapter with removable internal screen and a chrome-plated plug type cap with end chain.

One (1)

SUCTION VALVE CONTROL

Suction valve shall have swing type control handle located adjacent to valve.

One (1)

HOT DIP GALVANIZED DISCHARGE MANIFOLD

The discharge manifold shall be fabricated from heavy-duty tubular steel. The discharge manifold shall be fabricated, welded, all fittings attached and pressure tested prior to the galvanizing process. After testing the entire suction manifold shall be hot dip galvanized to minimize corrosion. The hot dip galvanized discharge manifold assembly shall be bolted to the pump and have stabilizer arms attached to reinforce the discharge manifold.

The hot dip galvanized manifold assembly shall have a ten (10) year warranty.

One (1)

PUMP DISCHARGES

Each gated discharge outlet shall include an Akron heavy-duty brass, quarter-turn, swing-out ball valve. All lines to have victaulic couplings or hose with stainless steel fittings installed where flex may occur to prevent cracking of the plumbing system. Each discharge shall have 3/4" cast bronze 1/4 turn drain valve complete with reinforced teflon seals, and blowout proof stem rated to 600



psi. A chrome-plated zinc handle shall be provided on each drain valve, complete with a 1" X 1 1/2" recessed identification label. Drains shall be aligned in a straight horizontal row at the lower edge of the corresponding pump panel so as to allow for ease of identification and operation. Each drain shall be labeled and numbered to correspond to the respective discharge outlet and coloring.

Individual discharge controls are to be aligned in a straight horizontal row across the pump operator's control panel, directly in-line with the corresponding discharge outlet line pressure gauges.

One (1)

GALVANIZED PLUMBING

All rigid piping five-inch diameter or less shall be galvanized type with tapered thread or victaulic type couplings.

One (1)

DRIVER SIDE DISCHARGE OUTLET

Each 2-1/2" discharge outlet on the driver's side pump panel shall have a 2-1/2" quarter turn valve with control on pump operator's panel. There shall be a chrome plated 2-1/2" NST adapter that extends through the pump panel. Each discharge shall be provided with chrome-plated 30-degree discharge elbow.

One (1)

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

One (1)

PASSENGER SIDE DISCHARGE OUTLET

Each 2-1/2" discharge outlet on the passenger's side pump panel shall have a 2-1/2" quarter turn, swing-out valve with control on pump operator's panel. There shall be a chrome-plated 2-1/2" NST adapter that extends through the pump panel. Each discharge shall be provided with chrome-plated 30-degree discharge elbow.

One (1)

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

One (1)

DRIVER SIDE REAR DISCHARGE OUTLET

There shall be one (1) 2-1/2" discharge outlet located on the driver's side rear of the body below the hosebed. The discharge outlet shall have a 2-1/2" quarter turn, swing-out valve with control on pump operator's panel. There shall be a



chrome-plated 2-1/2" NST adapter that extends through the rear of the body. The discharge shall be provided with a chrome-plated 30-degree discharge elbow.

One (1)

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

Three (3)

2-1/2" CAPS AND CHAINS

The following discharge outlets shall be equipped with a 2-1/2" chrome-plated cap and chain.

Two (2)

1-3/4" CROSSLAY(S) ASSEMBLY ABOVE PUMP

Crosslay hosebed(s) shall be designed to carry 200 feet of 1-3/4" double jacket fire hose. Crosslay hosebed(s) shall be located above the fire pump. The floor of the crosslay hosebed(s) shall be perforated to allow for drainage. Polished stainless steel hose roller assemblies shall be provided at the sides and lower edges of the crosslay opening on each side of the apparatus body.

Crosslay discharge(s) shall be plumbed using rigid pipe or flexible high-pressure hose coupled with stainless steel fittings. The crosslay shall be provided with 2" brass valve, and a 2" 90 degree swivel adapter with 1-1/2" NST male outlet thread.

Two (2)

MANUAL VALVE

Each discharge valve shall be swing out type with manual control handle located on pump operator's panel.

Two (2)

MANUAL DRAIN VALVE

Each crosslay/speedlay shall have a 3/4" drain with individual control on side pump panel.

One (1)

BOOSTER HOSE REEL

There shall be a Hannay booster hose reel with leak proof ball bearing swing joint, adjustable friction brake and electric rewind furnished. The reel shall be plumbed with wire reinforced, high-pressure hose coupled with brass fittings, and have one-inch (1") swing out, ball valve with control on pump operator's panel.

Booster hose reel is to be mounted in the right front compartment at runningboard level.

One (1)



MANUAL VALVE

One (1)

Discharge valve shall have manual control handle located on pump operator's panel.

BOOSTER REEL PLUMBED TO HIGH-PRESSURE SIDE OF PUMP

One (1)

The booster reel shall be plumbed to the high-pressure side of the pump using high-pressure flexible hose with stainless steel fittings.

PAINTED BOOSTER REEL

One (1)

Each booster reel shall have a steel frame and drum assembly with side discs. The frame, drum, drive chain, sprocket, hub assembly swivel joint and fasteners shall be painted silver. The booster reel assembly shall be Hannay model F.

TANK TO PUMP PLUMBING

A 3" Akron ball type gated suction valve shall be furnished from the tank to the pump, complete with a flexible connection and enclosed in the pump compartment.

A check valve shall be provided and installed in the line between the tank and the pump to prevent the possibility of backfilling the booster tank through the tank to pump suction line.

Tank suction shall be located in a sump assembly located below the bottom of the tank, properly baffled to prevent surging of water. A 3" cleanout plug shall be provided in the bottom of the tank sump.

One (1)

TANK FILL/COOLING LINE

A gated discharge line from the pressure side of the pump to the tank shall be furnished so the tank can be filled from draft or hydrant. Valve shall have control on the operator's panel. The valve is to be one and one-half inch, (1-1/2") swing out type ball valve and be plumbed to tank with flexible type hose.

One (1)

POLY BOOSTER TANK

The booster tank shall be of a specific configuration and is so designed to be completely independent of the body and compartments. All joints and seams shall be nitrogen welded and tested for maximum strength and integrity.

The transverse swash partitions shall be manufactured of polypropylene and extend from approximately 4" off the floor to just under the cover. The longitudinal swash partitions shall be constructed of polypropylene and extend



from the floor of the tank through the cover to allow for positive welding and maximum integrity. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are welded to each other as well as to the walls of the tank.

A forward mounted sump shall be provided in the tank. The sump shall be constructed of polypropylene and be located in the left front quarter of the tank. A polypropylene pipe shall be installed that will sweep from the front of the tank to the sump location. The sump shall have a 3" N.P.T. threaded coupling on the bottom for a plug. This shall be used as a combination clean out and tank drain. An anti-swirl plate shall be located above the sump.

There shall be two standard tank outlets; one for tank-to-pump suction lines, and one for a tank fill line. All tank couplings shall be backed with flow deflectors to break up the stream of water entering the tank.

The tank shall carry a lifetime warranty from its manufacturer.

One (1)

FILL TOWER

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of polypropylene and with a minimum dimension of 15" x 15" outer perimeter. The fill tower shall be located in the left front corner of the tank, approximately 32" behind the front of the hosebed. The fill tower shall have a polypropylene screen and a polypropylene hinged cover. Inside the fill tower, shall be fastened a combination vent overflow pipe. The vent overflow shall be polypropylene pipe that is designed to run through the tank and shall be piped behind the rear wheels.

One (1)

BOOSTER TANK

An 1800-gallon capacity polypropylene booster tank shall be provided.

One (1)

BOOSTER TANK SUBFRAME

The booster tank shall be mounted on a steel subframe. Steel subframe shall consist of two (2) longitudinal 3" x 4 pound channels and two (2) 3" x 4 pound channels welded together to form a tank retention cradle. The tank retention cradle shall prevent fore and aft, and side to side movement of the tank. Additional 3" x 4 pound transverse crossmember channels shall be installed to support the floor of the booster tank. The crossmembers shall have a maximum spacing of 20" for the polypropylene tanks. There shall be an additional full-length longitudinal member installed in the center of the tank support area. The



booster tank shall rest on heavy rubber channels that isolate the polypropylene tank from the subframe.

One (1)

REAR QUICK DUMP

A 10" Newton quick dump shall be installed on the rear center of the water tank.

One (1)

The dump valve shall be externally mounted with the dump valve assembly extending through the rear of the apparatus body panel.

One (1)

The control for the rear quick dump shall be electrically operated at the rear of the body.

One (1)

The dump valve shall have dual electrically operated controls for the quick dump assembly. One set of controls shall be located inside of the truck cab and one set of controls near the dump chute. The interior controls shall be located in a switch panel, and the exterior controls shall have protected, weather-resistant switches with guard.

One (1)

The rear Newton dump valve, furnished on the apparatus, shall be painted steel.

One (1)

There shall be a telescoping extension chute furnished on the dump valve. The telescoping extension chute shall be manually operated and have retention device to hold in the chute in the closed position for travel. The telescoping chute shall be attached to the dump valve with stainless steel bolts.

One (1)

EXTERNAL TANK FILL

An external tank fill shall be provided and installed at the rear of the body. The tank fill shall include a quarter turn 2-1/2" Akron ball valve with a chrome-plated female swivel, plug and chain.

One (1)

DRIVER SIDE MOUNTED OPERATOR'S CONTROL PANEL

All pump suction and discharge controls are to be mounted on the driver side pump operator's panel so as to permit operation of the pump from a central location.

All of the pump controls shall be clearly identified with permanently engraved plate type labels.



A full panel width polished light hood with a minimum of three Weldon model 2025 light assemblies shall be provided to illuminate the entire pump operator's control panel.

An additional polished light hood with a minimum of two Weldon model 2025 light assemblies shall be provided to illuminate the right side pump panel. Lights shall be controlled by the operator's panel light switch.

GAUGE PANEL

All gauges shall be suitably enclosed and mounted on a full pump compartment width "hinged" gauge panel constructed of the same material as the pump operators control panel, allowing access to the backside of all gauges and gauge lines. Panel is to include a stainless steel piano hinge, flush mounted chrome plated trigger latch, and stainless steel cable end stops. Electrical wiring and all gauge lines shall be properly tie wrapped to prevent kinking or cutting of the lines when the panel is opened.

One (1)

EXTRUDED ALUMINUM PUMP HOUSE STRUCTURE

The pump house structure shall be fabricated of extruded aluminum. The structure shall be welded together and have gusset plates on each corner. The pump house shall be mounted separate from the body and chassis and be bolted to the chassis frame rails.

The exposed areas of the pump house structure shall be over layed with polished aluminum treadplate.

One (1)

PUMP PANEL PUMP ENGAGEMENT LIGHT

There shall be one light on the operator's panel that will come on with a successful pump engagement.

One (1)

PUMP PANELS

The right and left side pump panels shall be constructed entirely of aluminum, and be coated with black thermo-plastic material. The panels are to be completely "bolted" in place for ease of removal.

One (1)

PUMP COMPARTMENT ACCESS DOOR

The passenger's side pump panel shall be provided with a full panel width vertically hinged access door located in the upper portion of the side panel. This door shall be approximately 18" high and as wide as possible, and shall be constructed of polished aluminum treadplate. Two (2) flush mounted, push type latches shall be furnished to hold the door closed. The inspection door shall be



attached with a stainless steel hinged and have a retainer cable attached to prevent the door from opening too far.

One (1)

PUMP OPERATORS PANEL

The following equipment shall be installed on the pump operator's panel.

One (1)

MASTER GAUGES

Class One #LFP410, 4-1/2" diameter liquid filled pressure gauge registering up to 600-lbs per square inch with 1/4" pipe thread connection. The gauge shall be of the type that will not be injured when subjected to a vacuum. The gauge is to have a white face with black lettering. The gauge is to be located at the right of the gauge panel and labeled "DISCHARGE" with an engraved label.

Class One #LFP410, 4-1/2" diameter liquid filled compound gauge shall be provided on the suction side of the pump registering at least 600-lbs pressure and 30-inches of vacuum. The gauge shall have a white face with black lettering. The gauge is to be located to the left of the master discharge gauge and labeled "INTAKE" with an engraved label.

One (1)

PRESSURE GAUGES

Class One #LFP220, 2-1/2" diameter liquid filled pressure gauges shall be provided. The gauges are to have white faces with black lettering. The gauges shall read -30 to 600 lbs. Line pressure gauges shall be individually identified with engraved labels.

Individual line pressure gauges are to be mounted adjacent to the corresponding discharge valve control.

Two (2)

There shall be one (1) pressure gauge for each 1-1/2" discharge outlet.

Three (3)

There shall be one (1) pressure gauge for each 2-1/2" discharge outlet.

One (1)

There shall be one (1) pressure gauge for each booster hose reel.

One (1)

ENGINE THROTTLE

An electronic vernier engine control throttle shall be provided on the pump operator's control panel for the Cummins electronic engine. The electronic throttle shall be positive locking, crank operated and have a quick release center button. There shall be an engraved identification label provided that reads THROTTLE.

One (1)

INFORMATION CENTER



A Class 1 Enfo III master engine gauge and warning device shall be furnished and installed on the pump operator's panel. The device will monitor the following engine systems;

- Engine RPM display
- System voltage display and alarm
- Engine oil pressure display and alarm
- Engine water temperature display and alarm.

One (1)

PUMP PANEL IDENTIFICATION LABELS

All discharges shall be provided with color-coded labels. Identification labels shall be provided at the discharge control, the discharge outlet, and at the discharge drain valve control, color-coded according to NFPA recommended standards.

One (1)

PUMP PANEL TANK LEVEL GAUGE

A MC Products four-light electrically operated tank level gauge shall be furnished at the pump operator's panel. The sending unit is to be easily cleaned and accessible from above the tank through a removable panel in the hosebed.

One (1)

UL TEST CONNECTIONS

A pump pressure and vacuum test block assembly shall be provided and mounted at the pump operator's control panel. The test block assembly shall include plug type caps.

One (1)

PUMP PANEL MOUNTED TRANSMISSION TEMPERATURE GAUGE

A transmission temperature gauge shall be installed at the pump operator's position to show temperature of the chassis transmission oil.

One (1)

HOSEBODY

The apparatus hosebody is to be properly reinforced without the use of angles or structural shapes, and free from all projections that might injure the fire hose.

The main apparatus hosebody shall run the full length of the apparatus body from behind the pump panel area to the rear face of the body.

The upper rear interior of the beavertail extrusions on the right and left side shall be overlaid with brushed stainless steel to protect the painted surface from damage by hose couplings

One (1)

HOSEBED CAPACITY



The hosebed will be configured to be 55 cubic feet, unless the desired hoseload requires more area.

One (1)

The hosebed shall hold the following: 1,200ft of 3" DJ hose

HOSEBED FLOORING

Floors of the hosebeds are to be provided with removable slat style extruded aluminum hosebed gratings, spaced 1/2" apart for proper hose ventilation. Hosebed gratings are easily lifted out of the main hosebed for access to the top of the specified booster water tank.

Two (2)

MAIN HOSEBED DIVIDER

Adjustable hosebed dividers shall be provided in the main hosebed.

The hosebed divider(s) shall be fabricated of 1/4" smooth aluminum sheet stock, pressed into a "T" shaped aluminum extrusion for added strength along the bottom edge of the divider.

One (1)

The divider shall be fully adjustable, mounted using aluminum "C" channel tracks at the front and rear of the divider for full side to side adjustment.

LADDER MOUNTING

The ladders shall be mounted on the right side of the body, directly above the right side compartments, using heavy duty Cast Products cast aluminum ladder brackets and with spring loaded chrome-plated quick release type clamps. The ladder brackets shall be vertically adjustable.

One (1)

HARD SUCTION HOSE TRAYS

Hard suction hoses shall be mounted in extruded aluminum, self-draining carrier trays with hold down device. The carrier trays shall be mounted on the passenger side of the body.

One (1)

FOLDING TANK CARRIER

There shall be a fully enclosed folding tank storage carrier provided on the driver side of the booster tank and above the lower compartments to carry a portable folding tank. The tank carrier shall hold the folding tank in the vertical position for travel, and fold down over the lower body side for loading and unloading. The folding tank carrier shall be fabricated of smooth aluminum painted to match the body side and have polished aluminum treadplate end caps. There shall be a hinged bracket that is bolted to the top of the lower compartments with rubber stops to prevent the folding tank carrier from touching the body side when in the



down position. There shall be a reinforcement plate installed on the compartment top where the folding tank carrier is attached. There shall be two heavy-duty clamps provided to hold the tank in the travel position.

One (1)

FOLDING TANK

The folding tank storage area shall accommodate a 2100-gallon tank.

One (1)

ALUMINUM BODY

The body shall be fabricated of aluminum extrusions, smooth aluminum sheet and aluminum treadplate.

The aluminum extrusion alloy shall be 6061 with a temper rating of T6, and have a tensile strength of 45,000 PSI and yield strength of 40,000 pounds. The aluminum extrusions shall 3" x 3" aluminum tubing and specially designed extrusions where applicable.

The smooth aluminum sheet material alloy shall be 5052 with a temper rating of H32, and have a tensile strength of 33,000 PSI and yield strength of 28,000 pounds.

The aluminum treadplate alloy shall be 3003 with a temper rating of H22, and have a tensile strength of 30,000 PSI and yield strength of 28,000 pounds.

The extrusions shall be designed as structural-framing members with the smooth aluminum and treadplate fabricated to form compartments, hosebeds, and floors. All aluminum material shall be welded together using the latest mig spray pulse arc welding system.

Compartments to be sweepout design and to be water and dust proof. All compartments shall be made to the maximum practical dimensions to provide maximum storage capacity.

All exterior compartments shall have polished aluminum drip moldings installed above the doors where necessary to prevent water from entering the compartments.

Wheel well panels shall be double break formed smooth aluminum that is welded in place. There shall be no visible bolt heads, retention nuts or fasteners on the exterior surface of the panel. To fully protect the wheel well area from road debris and to aid in cleaning, a full depth radius wheel well liner shall be provided. The frame side of the wheel well area on each side of the opening shall be attached to the frame side of the front and rear compartments. All



seams on the frame side of the body shall be welded and caulked to prevent moisture from entering the compartments.

The rear wheel wells shall be radius cut for a streamlined appearance. A polished aluminum fenderette shall be furnished at each rear wheel well opening, held in place with stainless steel fasteners.

FASTENERS

All aluminum and stainless steel components shall be attached using stainless steel fasteners.

Compartment door hinges, handrails and running boards shall be attached using minimum 1/4" diameter machine bolt fasteners.

3/16" diameter fasteners shall only be used in nonstructural areas such as; door handles, trim moldings, gauge mounting, etc.

One (1)

CS 1/8" ALUMINUM BODY

The aluminum sheet material used in fabricating the body shall be a minimum of .125 (1/8") in thickness.

One (1)

BODY DIMENSIONS

Apparatus body shall be up to 144" long and 96" wide, reference the drawing for actual body length. Body compartments shall be divided into upper and lower areas with the upper area approximately thirteen-inches in depth, and the lower area approximately twenty-three inches in depth. The hose bed shall be 68" wide.

One (1)

APPARATUS BODY SUB-FRAME

The apparatus body subframe shall be constructed entirely of heavy steel structural channel material.

Two full frame lengths, three-inch (3") 4 pound per foot longitudinal steel channels shall form the sides of the body subframe and sides of the water tank cradle. Subframe crossmembers shall be fabricated with three inch (3") 4 pound per foot heavy steel channel cross members welded to the longitudinal body subframe sides and the full length frame pads.

Two full frame length 1/2" x 3" flat steel frame pads shall be attached to the body subframe and rest on top of the chassis frame rails for proper frame weight distribution.



The steel frame pads, longitudinal steel channels and subframe crossmembers shall be attached to the chassis frame rails using heavy "U" bolt fasteners to allow removal of the subframe and body assembly from the chassis. There shall be a barrier provided between the subframe and body to prevent electrolysis.

The rear subframe and lower body platform support members shall be of the "two piece" design, fabricated of 4.3 lb. Per foot heavy channel and welded to the full length subframe channel liners at the rear.

A minimum of two rear platform support channels shall be provided and constructed of 4.3 lb. Per foot heavy steel material. Each support channel shall have welded in gusset where the support meets the rear subframe rails.

After fabrication the entire subframe assembly shall be hot dip galvanized to prevent corrosion. The hot dip galvanized subframe shall have a lifetime warranty.

One (1)

COMPARTMENT VENTS

All body compartments shall have a minimum of one (1) louvered panel bolted into a wall to provide the proper airflow inside the compartment. There shall be a filter installed behind the louvered panel. The filter shall be accessible for cleaning by removing the louvered panel on the interior of the compartment.

One (1)

BODY AND PUMP HOUSE FLEX JOINT

When equipped with a fire pump, the body and pump house shall be a separate freestanding component forming a true flex joint between the body and pump house. The intent is to allow either to be easily removed as a single unit without disturbing the other and to provide a flex joint between the two modules. Designs where the pump house and body are interjoined as a common unit do not meet the technical requirement of providing a flex joint or the repairability requirement of these specifications.

One (1)

WHEEL WELL LINER AND FENDERETTES

For ease of accessibility and maintenance, wheel well panels shall be double break formed painted smooth plate that is welded in place.

To fully protect the wheel well area from road debris and to aid in cleaning, a full depth (minimum of 25") radius wheel well liner shall be provided. Wheel well liner shall be smooth aluminum to prevent corrosion.



The rear wheel wells shall be radius cut for a streamlined appearance. A polished aluminum fenderette shall be furnished at each rear wheel well opening, held in place with concealed stainless steel fasteners.

One (1)

REAR TOW EYES

There shall be two tow eyes furnished under the rear of the body and attached directly to each chassis frame rail. There shall be a reinforcement spreader bar connecting the two tow eyes. Tow eyes are to be constructed of 3/8" plate steel with a 4" I.D. hole, large enough for passing through a tow chain end hook.

One (1)

APPARATUS COMPARTMENTATION

There shall be large enclosed compartments on both sides of the body, starting at the front of the hosebody and continuing to the rear of the apparatus. These compartments shall be as large as possible, using all available space.

The aluminum treadplate compartmentation tops on each side of the body shall be extended out and downwards a minimum of .50" over the compartment doors forming a drip rail. Corners shall be TIG welded.

Lower or rear face compartments, if specified shall be provided with polished aluminum drip rails.

One (1)

SIDE BODY COMPARTMENT ROLL-UP DOOR CONSTRUCTION

Exterior side equipment compartments so specified shall be equipped with roll-up shutter doors to be installed as specified herein.

The drum assembly shall be fully enclosed and protected from the elements. Pendent plates supporting the door roll assembly shall be bolted in place, adjustable and capable of being removed with common hand tools. Pendent plates and supports that are welded in place do not meet the maintenance and service criteria of these specifications.

One (1)

NATURAL FINISH ROLL UP DOORS

The roll-up doors on each side of the apparatus body shall be natural finish aluminum.

One (1)

ROLL UP DOORS

R.O.M. Robison brand extruded aluminum shutter style doors with lift bar latch mechanisms and associated hardware shall be provided and installed as specified.

One (1)



DRIVER SIDE

One (1) The driver side of the apparatus body shall consist of the following configuration.

DRIVER SIDE COMPARTMENTS

Two lower body compartments shall be furnished as follows:

- One compartment ahead of the rear wheels with roll-up door.
- One compartment behind the rear wheels with roll-up door.

One (1)

PASSENGER SIDE COMPARTMENTS

The passenger side of the apparatus body shall consist of the following compartment configuration.

One (1)

PASSENGER SIDE COMPARTMENTS

Two lower body compartments shall be furnished as follows:

- One compartment ahead of the rear wheels with roll-up door.
- One compartment behind the rear wheels with roll-up door.

One (1)

REAR BEAVER TAIL

There shall be a beaver tail on the rear of the body. The beaver tail shall angle down from the top of the hose bed to the rear step area. Polished aluminum tread bright shall be installed on the inside of the beaver tail.

Two (2)

ADJUSTABLE SHELVES

Compartment shelves shall be constructed of .125" smooth Aluminum. Shelves shall have formed edges on three sides for added strength. Shelves shall be fully adjustable, with extruded aluminum unistrut channels provided on the front and rear compartment walls.

Two (2)

DRIVER SIDE AIR BOTTLE COMPARTMENTS IN WHEELWELL

SCBA storage compartment shall be provided and located in the driver side rear wheelwell of the apparatus body. Compartment door and frame shall be constructed entirely of cast aluminum and have hinged style door. The compartment bottom and rear wall shall be lined with rubber material to protect paint finish of the air cylinder.

Two (2)

PASSENGER SIDE AIR BOTTLE COMPARTMENTS IN WHEELWELL



SCBA storage compartment shall be provided and located in the passenger side rear wheelwell of the apparatus body. Compartment door and frame shall be constructed entirely of cast aluminum and have hinged style door. The compartment bottom and rear wall shall be lined with rubber material to protect paint finish of the air cylinder.

Two (2)

SCBA BRACKETS

SCBA mounting bracket(s) shall be provided and mounted in the enclosed storage compartments as per instructions of Fire Department.

One (1)

EXTRUDED ALUMINUM RUB RAILS

Full body length polished aluminum rub rails shall be bolted in place on the right and left body sides and in the pump panel area. The rub rails shall extend outward beyond the body sides for protection of the compartments and doors. There shall be a bolt on aluminum corner casting on each rear corner to blend the rear tailboard assembly with the side rub rails.

One (1)

The side rub rails shall be a heavy extruded aluminum "C" channel.

SIDE AND REAR OVERLAYS

Overlay panels shall be constructed of 3003 polished aluminum treadplate. Polished aluminum overlay shall be provided and installed in the following areas:

- The front face of each side compartment.
- The rear body face and vertical area above tailboard and below hosebed.
- Drivers side and passenger compartment top extending down over side to the compartment doors then forming a drip rail above doors.
- Front face of hose bed above booster tank.

Overlay shall be installed with "Aluminized" stainless steel bolts to prevent corrosion.

One (1)

SLIP-RESISTANT WALKWAY SURFACE

All exterior surfaces designated as stepping, standing, and walking areas shall have an aluminum slip-resistant overlay material installed. The slip-resistant overlay material shall have a raised serrated surface that will allow moisture to drain out either side. The recessed surface shall be one piece solid material to prevent road spray and debris from entering the top surface from below. The slip-resistant overlay material shall meet the requirements of NFPA 13-7.3. The slip-resistant surface shall be installed in the following areas of the apparatus body:



Step areas of the side running boards.
Rear step running board step.
Walkway and standing platforms

One (1)

REAR STEP/RUNNING BOARDS

The apparatus body running boards and rear step shall be constructed with slip-resistant surface and shall have bright aluminum treadplate trim around the outside edges. Side running boards and rear step shall be removable for ease of service in case of damage.

One (1)

REAR STEP/TAILBOARD

A single piece .188 rear step/tailboard shall be furnished that is a minimum of 16.00" deep and full width of the apparatus body, from rub rail to rubrail. The tailboard shall be provided with a removable casting on each corner for a pleasing appearance.

One (1)

HANDRAILS

Access handrails shall be 1 1/4" in diameter extruded aluminum with rubber insert. Access rail escutcheons and brackets shall be chrome plated and attached with stainless steel bolts and locking nuts. Anchoring of posts and framing members for railings of all types shall be of such construction that the completed railing structure shall be capable of withstanding a load of at least 225 pounds applied in any direction at any point along the rail.

One (1)

REAR HANDRAILS

Two (2) vertical access handrails shall be provided and mounted on the rear of the apparatus body, one on each side. Each rear handrail to be approximately 48" long.

One (1)

REAR FOLDING STEPS

Four (4) NFPA approved folding steps shall be provided and mounted on the rear of the apparatus, two on each side. All access steps shall have a minimum surface area of 35-square inches, and have a slip-resistant standing surface. The step shall be capable of supporting a 500-lb. load.

One (1)

ELECTRICAL

Electrical wiring, hydraulic lines, air system tubing, and control cables shall be fastened to the frame or body structure of the apparatus and shall be furnished



with protective looms, grommets, or other devices, so that any such connector and/or wiring will be protected from shear or tear.

The body 12-Volt electrical system shall be designed specifically for the apparatus body. Automatic reset circuit breakers shall be provided and installed in all circuits.

Wiring data shall be provided with the completed apparatus.

The following electrical equipment and lights shall be provided and installed:

One (1)

WIRING SYSTEM

All electrical wiring shall be 14-gauge heavy strand copper with type GXL crosslink high temperature insulation, being circuit function printed every three-inches along its entire length.

Wiring data shall be provided with the completed apparatus.

The following electrical equipment and lights shall be provided and installed:

One (1)

TAIL & STOP LIGHTS

Two (2) Weldon #2010 rectangular red stop/tail lights shall be provided and mounted at the rear of the body, one on each side.

One (1)

DIRECTIONAL LIGHTS WELDON 2010

Two (2) Weldon #2010, rectangular amber directional signal lights with black arrows shall be provided and mounted at the rear of the body, one on each side below the stop/tail lights.

One (1)

BACKUP LIGHTS WELDON 2010 (RECT)

Two (2) Weldon #2010, rectangular clear backup lights shall be provided and mounted, one on each side at the rear of the body. The backup lights shall be mounted below the rear stop/tail and directional lights.

One (1)

CLEARANCE LIGHTS

There shall be clearance marker lights installed meeting all DOT requirements. The vehicle clearance lights shall be recess mounted within the rear center tailboard step.

One (1)

LICENSE PLATE BRACKET



A license plate mounting bracket shall be provided complete with a chrome-plated shielded indirect type light. Bracket shall be mounted at the rear of the apparatus body.

One (1)

BACKUP ALARM

An automatic, electronic reverse alarm shall be provided and installed. An alarm shall activate whenever the reverse gear is selected in the transmission.

One (1)

LOAD MANAGER

The apparatus shall be equipped with a Kussmaul model 091-79 Automatic Load Shedding System for performing continuous electrical load management. The Load Manager shall have the following features:

- Monitor 12-volt system and detect low voltage.
- Capability to control two (2) loads.
- Automatic reset when voltage rises.
- Adjustable voltage setpoint.

The load manager shall be protected against reverse polarity and shorted outputs, and be enclosed in a metal enclosure to enhance EMI/RFI protection. CSFA shall provide for all electrical loads in excess of the NFPA minimum electrical requirements that exceed the alternator output.

One (1)

COMPARTMENT LIGHTING

All side and rear exterior equipment compartments shall be provided with one (1) clear compartment light mounted to the side walls of the compartment. Compartment lights shall switch on automatically when the compartment door is opened and switch off when the door is closed.

Two (2)

ADDITIONAL COMPARTMENT LIGHTS

Additional sealed lights shall be provided and installed for compartments with shelves, as directed by the Fire Department. Additional lights shall be mounted to a bracket attached to the unistrut shelf standard. Lights mounted to the shelf brackets shall have additional wire to allow the light to be adjusted with the shelf. Lights shall be wired to switch on and off with the automatic door jamb switch.

One (1)

OPEN COMPARTMENT/HAZARD WARNING LIGHT

A red flashing, warning light shall be provided and installed in the driver's compartment to indicate an open passenger or apparatus compartment door. The hazard light shall also be attached to folding equipment racks and light towers as specified. Light shall be properly marked and identified.



One (1)

AUDIBLE ALARM

A 12-volt audible warning device shall be provided in the chassis cab connected to the open compartment door/hazard warning light.

One (1)

BATTERY DISCONNECT SWITCH

A master battery on/off switch shall be provided and mounted in a convenient location to the driver. The master battery switch shall disconnect the batteries from all chassis and body accessories.

One (1)

A "Battery-On" pilot light shall be provided, visible to the driver.

AIR COMPRESSOR/BATTERY CONDITIONER

A 110-volt Kussmaul Auto-Charge 1000, single system, 15-amp, automatic battery charger and power supply shall be provided and installed within the chassis cab and wired to the battery system. Battery charger shall be 15-amp output type designed to automatically charge the battery system when shoreline power is connected. The charger shall be equipped with a bar graph type charge level indicator to indicate the charge rate. The charger shall have an electronic sensing circuit to sense the true battery voltage while eliminating the need for external sense wires. Charging is completely automatic, when the battery is fully charged, all charging stops. There is no over charging and no water boil off.

The charger shall have a built in 3-amp battery saver for rechargeable hand lights.

There shall be an air compressor furnished to maintain the air pressure in the vehicle brake system. The compressor shall be wired to the vehicle electrical system and plumbed to the vehicle air system.

One (1)

AUTO-EJECT

A Kussmaul "Super Auto-Eject" 20-amp automatic disconnect device shall be provided and installed on the 110 volt shoreline connection complete with weatherproof cover and matching plug. The Auto-Eject shall be activated by the chassis starter switch to disconnect the plug. The Super Auto-Eject shall be completely sealed to prevent contamination of the mechanism by inclement weather and road conditions. The Super Auto-Eject shall have an internal switch to open and close the A.C. circuit after the mating connector is inserted and before the connector is removed.

One (1)

DASH MOUNTED EMERGENCY ELECTRICAL SWITCH PANEL



An electrical switch panel shall be designed and mounted in the cab dash area. All switches shall be provided with backlighted snap-in legend inserts.

SWITCHES

All emergency light switches shall be lighted, rocker style. Switches shall be internally lit when the switch circuit is in the on position. A plug-in identification label is to be provided and installed adjacent to each rocker switch with backlighting provided behind the label.

An internally lighted "master" switch shall be provided and wired through a heavy-duty relay to activate power to the emergency lights.

One (1)

REAR STEP LIGHTS

Two (2) chrome plated lights shall be furnished and installed on the rear face of the body to illuminate the rear step area. Lights shall be wired to the panel light switch at the pump operator's panel.

One (1)

ENGINE COMPARTMENT WORK LIGHT

An engine compartment work light shall be provided complete with a switch mounted on the light head.

One (1)

PUMP COMPARTMENT WORK LIGHT

A pump compartment work light shall be provided and installed within the pump compartment area complete with a switch mounted on the light head.

One (1)

UNDER CAB LIGHTING

There shall be two (2) lights furnished below the chassis cab, one on each side below each door. The lights shall be wired to switch on and off automatically when the cab doors are opened.

One (1)

UNDER BODY LIGHTING

There shall be two (2) lights furnished below the pump house running board, one on each side. The lights shall be wired to turn on and off with a switch located on the driver's side pump panel.

One (1)

UNDER BODY LIGHTING REAR STEP

There shall be two (2) lights furnished below the rear step, one on each side. The lights shall be wired to turn on and off with a switch located on the driver's side pump panel.



One (1)

AIR HORNS

Two (2) chrome-plated Grover "Stuttertone" air horns shall be provided and mounted on the sides of the engine hood. A pressure protection valve to prevent the use of air horns or other air operated accessories when the system air pressure drops below 80 psi shall be provided.

One (1)

Air horns shall be controlled from the following switch positions.

One (1) overhead lanyard control shall be provided in the front of the cab for activation of the air horn. The lanyard control shall be accessible to both the driver and the officer when seated.

One (1)

ELECTRONIC SIREN

A Code 3 Model 3692 V-CON, 200-watt electronic siren with Hi-Lo and hardwired microphone shall be provided and mounted in the cab.

One (1)

SPEAKER

DYNAMAX, 100-watt speaker shall be provided and recess mounted in the front bumper of the chassis. The speaker shall be connected to the electronic siren control unit.

One (1)

EMERGENCY LIGHTING

The upper and lower zones "A", "B", "C", "D" of the apparatus shall have the following emergency lighting equipment:

One (1)

LIGHT BAR

One (1) Code 3 model 556A3 56" mounted on chassis cab roof to meet the NFPA upper zone A lighting requirement. Light bar to have the following equipment.

- (4) 50-watt standard rotators
- (1) 50-watt fast rotators
- (2) diamond mirrors
- (2) 2-step cascade mirrors

One (1)

REAR LIGHTS

Two (2) Code 3 model 550F rotating lights mounted on the rear of the apparatus body to meet the NFPA Zone B, C, D upper level lighting requirement. The lights shall be activated through the master emergency light switch located on the electrical console. Each light to have the following equipment.



- (1) 50-watt fast rotator
- 1 Red lens / 1 Amber lens

One (1)

UPPER ZONE "B, C, D" LIGHT MOUNTING

The upper rear lights designated for Upper Zone "B" shall be mounted on cast aluminum stanchions attached to the apparatus body, one on each side.

One (1)

ZONE A FRONT LIGHTS

There shall be two (2) Code 3 model OL135 oscillating lights furnished on the front grill to meet the NFPA Zone A lower level lighting requirement. The lights shall be connected to a relay be activated through the master emergency light switch located on the electrical console.

One (1)

ZONE B & D SIDE LIGHTS

There shall be three (3) Code 3 model 45 LED lights furnished on each side of the apparatus to meet the NFPA Zone B & D lower level lighting requirement. One light mounted as far forward as possible, one light mounted as far to the rear as possible, and one light mounted between the front and rear lights. The lights shall be connected to a power supply and be activated through the master emergency light switch located on the electrical console.

One (1)

ZONE C REAR LIGHTS

There shall be two (2) Code 3 model 45 LED lights furnished on the rear of the apparatus body to meet the NFPA Zone C lower level lighting requirement. The halogen lights shall be activated through the master emergency light switch located on the electrical console.

One (1)

12 VOLT ELECTRICAL CERTIFICATION

The low voltage electrical system shall be tested and certified per NFPA 1901 requirements.

A certificate of compliance shall be provided with the completed vehicle upon delivery.

Minimum electrical load consists of the total amperage required to simultaneously operate the following in a stationary mode at the incident scene.

- The propulsion engine and transmission.
- All Clearance and marker lights.
- The communication radio. (Default of 5.0 amps used for testing).



- Illumination of all walking surfaces, the ground at all egress points, controls and instrument panels and 50% of the total compartment lighting load.
- Minimum warning lights required for "Blocking Right of Way" mode.
- The current to simultaneously operate any fire pump, aerial device & hydraulic pumps.
- Anything defined by the purchaser to be critical to the mission of the apparatus.

The first test for the electrical system is the Reserve Capacity Test. All the above listed components operate with the engine shut off. After 10 minutes all electrical loads are shut off and the battery system must have adequate reserve power to start the engine.

The second test is the Alternator Performance Test at Idle. All the above listed components operate with the engine at an idle. There can be no current draw from the batteries of the apparatus.

The third test is the Alternator Performance Test at Full Load. All electrical components shall be activated with the engine operating at governed RPM for two hours. During the test the system voltage can not drop below 11.7-volts or have excessive battery discharge for more than 120 seconds. Any loads not listed in the minimum electrical load may be load managed in order to pass the test.

All of the above tests must be conducted with the engine compartment at approximately 200 degrees.

One (1)

GENERATOR

A Honda EM-5000SXX1, 5000-watt, 120/240-volt generator shall be provided. The unit shall have an air cooled 11HP gasoline engine equipped with high temperature and low oil pressure shutdown. The unit shall be three wire, single phase 60-hz with full rated power available from a single 120-volt outlet. The oil drain, oil dip stick, fuel filter and oil filter for the generator must be easily accessible for maintenance.

An integral 4.5-gallon fuel tank, with electric and recoil starter shall be furnished with the generator.

Electric start provisions shall be furnished for the generator from the chassis battery system. Generator start/stop switches shall be provided at the generator.

One (1)

CIRCUIT BREAKER PANEL



A circuit breaker panel shall be provided and mounted with two (2) manual reset circuit breakers properly labeled.

A portable generator shall be connected to the circuit breaker panel with S/O cord and quick disconnect plug. A permanent mount generator shall be hard wired to the circuit panel.

The circuit breaker panel shall be located in a compartment as close to the generator as practical, and mounted to not interfere with shelves or trays if specified. Circuit breaker panel shall be mounted toward the bottom of the compartment just above the compartment floor. Breaker panel cover shall be accessible with hand tools.

One (1)

All AC wiring to be installed in liquid tight conduit.

One (1)

GENERATOR MOUNTING

The generator shall be mounted in the right front lower compartment

One (1)

START/STOP ASSEMBLY

A remote start/stop control assembly shall be provided for the generator in the chassis cab area.

Two (2)

500W Telescoping Light

One (1)

PAINTING

All bright metal fittings if unavailable in stainless steel shall be heavily chrome-plated. Iron fittings shall be copper plated prior to chrome plating.

All seams shall be caulked both inside and along the exterior edges with an automotive sealant to prevent moisture from entering between any body panels.

The body and all parts shall be thoroughly washed with grease cutting solvents prior to any sanding. After the body has been sanded and the minor imperfections filled and sanded, the body shall be washed again with a solution to remove any contaminants on the surface. The first coating to be applied is a self-etching primer for maximum adhesion to the body metal. The next three coats shall be an acrylic, urethane, primer surfacer. The primer surfacer coat is to be hand sanded with 600-grit sandpaper to insure maximum gloss of the paint. The last step is the application of at least three coats of Concept Acrylic Urethane two component color.

The fire pump and all rigid discharge and suction plumbing shall be painted silver in color.



While constructing the truck body, all aluminum parts shall be properly fitted on the body. The backside of all aluminum parts shall be sanded smooth of any burrs and sharp edges.

All aluminum parts shall be bolted to the body using stainless steel fasteners. Cadmium plated fasteners are not acceptable.

During reassembly of the apparatus, care shall be exercised in fitting and fastening the parts back in their respective position on the vehicle.

One (1)

NATURAL FINISH ROLL UP DOORS

The roll-up doors on each side of the apparatus body shall be a natural finish aluminum.

One (1)

UNDERCOATING

The body subframe shall be undercoated with a heavy-duty automotive type undercoating before the rubber backing and the compartments are attached. After the body has been attached to the subframe and all final items have been installed the entire body assembly shall be undercoated

One (1)

INTERIOR COMPARTMENT FINISH

The interior vertical walls of the apparatus compartments shall have a natural smooth finish.

One (1)

WHEEL PAINTING

The exterior faces of the front and rear wheels, shall be finished painted to match the apparatus body. Wheels shall be properly prepared and finished with primer coats and topcoats as specified.

The outer two-inches of each outside wheel rim shall be painted Silver in color, unless otherwise specified.

One (1)

PAINT BODY TO MATCH CHASSIS

The apparatus body to be painted to match the chassis.

One (1)

REFLECTIVE SAFETY STRIPE

A 10" wide 3M brand Scotchlite #680-10 reflective stripe shall be affixed to the perimeter of the vehicle. Striping shall be placed up to 60" above ground level and shall conform to NFPA reflectivity requirements. At least 60% of the



perimeter length of each side and width of the rear, and at least 40% of the perimeter width of the front of the vehicle shall have reflective stripe.

The stripe shall be white in color.

One (1)

IDENTIFICATION & SAFETY LABELS

A permanent plate shall be installed in the driver's compartment to specify the quantity and type of the following fluids in the vehicle:

1. Engine oil.
2. Engine coolant.
3. Transmission fluid.
4. Pump Transmission Lubrication Fluid.
5. Pump Primer Fluid (If applicable).
6. Drive Axle Lubrication Fluid.
7. Air-conditioning refrigerant.
8. Air-conditioning lubrication oil.
9. Power steering fluid.
10. Transfer case fluid.
11. Equipment rack fluid.
12. Air compressor system lubricant.
13. Generator system lubricant.

When trucks have been UL certified, a permanent plate with pump performance data and serial numbers shall be installed on the pump panel.

A permanent plate shall be installed in the driver's compartment specifying the maximum number of personnel the vehicle is designed to carry per NFPA standards. It shall be located in an area visible to the driver.

An accident prevention sign stating "DANGER PERSONNEL MUST BE SEATED AND SEAT BELTS MUST BE FASTENED WHILE VEHICLE IS IN MOTION OR DEATH OR SERIOUS INJURY MAY RESULT". The warning sign shall be placed so it is visible from all seating positions.

An accident prevention sign stating "DANGER DO NOT RIDE ON REAR STEP WHILE VEHICLE IS IN MOTION, DEATH OR SERIOUS INJURY MAY RESULT". The warning sign shall be placed so it is visible from the rear step of the vehicle.

If an inlet located at the pump operator's position is valved, it shall be provided with a permanent label that states "WARNING SERIOUS INJURY Or DEATH COULD OCCUR IF INLET IS SUPPLIED BY A PRESSURIZED SOURCE WHEN THE VALVE IS CLOSED".

One (1)



OPERATION/SERVICE MANUALS

The following applicable documentation shall be supplied upon delivery:

- Two (2) copies of Operation/Service manual of the apparatus operations and service manuals supplied by components manufacturers.
- Pump certification including manufactures record of apparatus construction details.
- Certificate of compliance to Electrical Warning System Low Voltage test.
- Water tank capacity certificate.
- Line Voltage Electrical System test certificate.
- (NFPA 19-14.4.1 - 19.14.4.2)
- Certificate of approval for stationary pumping.

The selling dealer shall furnish the following equipment.

One (1)

A 24-foot, 2-section aluminum fire department extension ladder, ALCO-LITE Model PEL-24, shall be furnished.

One (1)

A 14-foot aluminum roof ladder with folding hooks, ALCO-LITE model PRL-14, shall be furnished.

One (1)

A 10-foot folding aluminum attic ladder, with mounting brackets, ALCO-LITE model FL-10, shall be furnished.

Four (4)

Streamlight Litebox 45107 shall be installed where specified and wired to the chassis 12-volt system.

FOR MORE INFORMATION OR PICTURES OF THIS TRUCK PLEASE CALL:

ARTESIA FIRE EQUIPMENT

1-800-748-2076

505-746-2426

OR EMAIL US AT:

MARSHALL@ARTESIAFIRE.COM

RON@ARTESIAFIRE.COM

GPERRYAFE@AOL.COM